

## Breitkeilriemen – flankenoffen, formgezahnt

Breitkeilriemen			Breitkeilriemen		
Profil mm	Li = Innenlänge mm	Winkel	Profil mm	Li = Innenlänge mm	Winkel
<b>13 x 5</b>	468	24°	<b>23 x 10</b>	833	30°
	476			865	
	700			935	
	1120				
<b>17 x 5</b>	426	24°	<b>26 x 8</b>	630	27°
	476			655	
	536			672	
	606			680	
	686			710	
	776			750	
	875			762	
	976			800	
	976			850	
<b>21 x 6</b>	530	27°	862	25°	
	600		900		
	675		962		
	770		1000		
	870		1082		
	970		1212		
	1090		1362		
	1090		1562		
<b>22 x 8</b>	525	25°	<b>28 x 8</b>	600	25°
	550			650	
	575			700	
	600			750	
	610			800	
	650			850	
	675			900	
	700			950	
	750			1000	
	800			1060	
	850			1120	
	900			1180	
	950			1250	
	1000			1320	
	1060			1400	
	1120			1500	
	1180			1600	
	1200			1700	
	1250			1800	
	1320			2000	
	1400			2240	
<b>23 x 10</b>	760	30°	<b>30 x 10</b>	650	27°
	713			665	
				680	
				700	
				750	
				775	

## Breitkeilriemen – flankenoffen, formgezahnt

Breitkeilriemen			Breitkeilriemen		
Profil mm	Li = Innenlänge mm	Winkel	Profil mm	Li = Innenlänge mm	Winkel
<b>30 x 10</b>	800	27°	<b>37 x 10</b>	1500	28°
	850			1600	
	875			1700	
	900			1800	
	950			2000	
	1000			2240	
	1035			2500	
	1050			<b>41 x 13</b>	
	1073		970		
	1120		1000		
	1175		1040		
	1185		1060		
	1200		1120		
	1320		1190	<b>47 x 10</b>	28°
<b>32 x 10</b>	750	27°	1250		
	790		1340		
	820		1400		
	850		1440		
	900		1600		
	950		1740		
	1000		1940		
	1073		2180		
	1100		1000		
	1120		1120		
	1200		850	<b>47 x 13</b>	28°
	1250		900		
	1353		950		
	1400		1000		
1420	1060				
1553	1120				
1750	1180				
1953	1250				
<b>36 x 14</b>	1140	30°	1320		
	1720		1400		
<b>37 x 10</b>	660	28°	1500		
	750		1600		
	800		1700		
	850		1800		
	900		2000		
	950		2240		
	1000		2500		
	1060		<b>52 x 16</b>	27°	1180
	1120				1250
	1180				1325
	1250				1400
	1320				1525
1400	1600				

## Breitkeilriemen – flankenoffen, formgezahnt

Breitkeilriemen

Profil mm	Li = Innenlänge mm	Winkel
<b>52 x 16</b>	1725	27°
	1800	
	1900	
	1925	
	2000	
	2165	
	2425	
<b>55 x 16</b>	1250	28°
	1320	
	1400	
	1500	
	1600	
	1700	
	1800	
	1900	
	2000	
	2240	
	2500	
	2800	
	<b>65 x 20</b>	
1906		
2146		
2406		
<b>70 x 18</b>	1445	28°
	1500	
	1550	
	1600	
	1700	
	1800	
	2000	
	2240	
	2500	
	2800	
	3150	

Weitere Größen auf Anfrage.

Breitkeilriemen USA Standard

RMA – MPTA Code Nr.	RMA – MPTA Code Nr.	RMA – MPTA Code Nr.
1422 V 235	1926 V 290	2926 V 586
1422 V 240	1926 V 407	2926 V 606
1422 V 270	1926 V 415	2926 V 616
1422 V 290	1926 V 427	2926 V 636
1422 V 300	2230 V 266	2926 V 646
1422 V 330	2230 V 273	2926 V 666
1422 V 340	2230 V 275	2926 V 686
1422 V 360	2230 V 326	2926 V 726
1422 V 400	2230 V 375	2926 V 750
1422 V 420	2322 V 329	2926 V 776
1422 V 440	2322 V 347	2926 V 786
1422 V 460	2322 V 364	3226 V 392
1422 V 470	2322 V 396	3226 V 400
1422 V 480	2322 V 421	3226 V 433
1422 V 540	2322 V 434	3226 V 450
1422 V 600	2322 V 441	3226 V 505
1422 V 660	2322 V 461	3226 V 545
1430 V 215	2322 V 481	3226 V 585
1922 V 277	2322 V 486	3226 V 603
1922 V 282	2322 V 521	3226 V 650
1922 V 998	2322 V 541	3226 V 663
1922 V 321	2322 V 601	3226 V 723
1922 V 332	2322 V 661	3226 V 783
1922 V 338	2322 V 681	3226 V 843
1922 V 363	2322 V 701	3230 V 560
1922 V 381	2322 V 801	3230 V 585
1922 V 386	2530 V 500	3230 V 600
1922 V 403	2530 V 530	3230 V 630
1922 V 462	2530 V 560	3230 V 670
1922 V 443	2530 V 600	3230 V 710
1922 V 454	2530 V 630	3230 V 723
1922 V 460	2530 V 670	3230 V 750
1922 V 484	2530 V 710	3230 V 800
1922 V 526	2530 V 750	3230 V 850
1922 V 544	2530 V 790	3432 V 450
1922 V 604	2830 V 337	3432 V 456
1922 V 630	2830 V 363	3432 V 480
1922 V 646	2830 V 366	3432 V 428
1922 V 666	2830 V 367	3432 V 534
1922 V 686	2830 V 393	4430 V 530
1922 V 706	2830 V 396	4430 V 548
1922 V 721	2830 V 422	4430 V 555
1922 V 726	2926 V 471	4430 V 560
1922 V 751	2926 V 486	4430 V 570
1922 V 756	2926 V 521	4430 V 578
1926 V 250	2926 V 546	4430 V 600
1926 V 275	2926 V 474	4430 V 610

**Breitkeilriemen USA Standard:**  
keine Lagerware, Lieferzeit und  
Abnahmemenge auf Anfrage