

## Hochleistungs - Schmalkeilriemen USA – Standard RMA - MPTA

Profil <b>3V / 9N</b>		Profil <b>5V / 15N</b>		Profil <b>8V / 25N</b>	
Profil / Typ	LA = Außenlänge mm	Profil / Typ	LA = Außenlänge mm	Profil / Typ	LA = Außenlänge mm
3V 250	635	5V 500	1270	8V 1000	2540
3V 265	673	5V 530	1346	8V 1060	2692
3V 280	711	5V 560	1422	8V 1120	2845
3V 300	762	5V 600	1524	8V 1180	2997
3V 315	800	5V 630	1600	8V 1250	3175
3V 335	851	5V 670	1702	8V 1320	3353
3V 355	902	5V 710	1803	8V 1400	3556
3V 375	952	5V 750	1905	8V 1500	3810
3V 400	1016	5V 800	2032	8V 1600	4064
3V 425	1080	5V 850	2159	8V 1700	4318
3V 450	1043	5V 900	2286	8V 1800	4572
3V 475	1206	5V 950	2413	8V 1900	4826
3V 500	1270	5V 1000	2540	8V 2000	5080
3V 530	1346	5V 1060	2692	8V 2120	5385
3V 560	1422	5V 1120	2845	8V 2240	5690
3V 600	1524	5V 1180	2997	8V 2360	5964
3V 630	1600	5V 1250	3175	8V 2500	6350
3V 670	1702	5V 1320	3353	8V 2650	6731
3V 710	1803	5V 1400	3556	8V 2800	7112
3V 750	1905	5V 1500	3810	8V 3000	7620
3V 800	2032	5V 1600	4064	8V 3150	8001
3V 850	2159	5V 1700	4318	8V 3350	8509
3V 900	2286	5V 1800	4572	8V 3550	9017
3V 950	2113	5V 1900	4826	8V 3750	9525
3V 1000	2540	5V 2000	5080	8V 4000	10160
3V 1060	2692	5V 2120	5385	8V 4250	10762
3V 1120	2845	5V 2240	5690	8V 4500	11430
3V 1180	2997	5V 2360	5994	8V 4750	12065
3V 1250	3175	5V 2500	6350	8V 5000	12700
3V 1320	3353	5V 2650	6731		
3V 1400	3546	5V 2800	7112		
		5V 3000	7620		
		5V 3150	8001		
		5V 3350	8509		
		5V 3550	9017		

Mindestabnahmemenge  
für nicht in der Liste auf-  
geführte Abmessungen  
**3V / 5V / 8V auf Anfrage**